



**Shandong Zhuoxing Chemical Co., Ltd.**  
**Zibo Zhuoxing Enterprises Co., Ltd.**

## Concrete admixture powdered polycarboxylate base superplasticizer

### Introduction

Concrete admixture powdered polycarboxylate base superplasticizer is a new generation of Eco-friendly high performance polycarboxylate ether superplasticizer powder developed by our company with DD-909 (TPEG 2400) as main raw material.

Type: powder

Samples: powder \$2.00/Kilogram | 1 Kilogram (Min. Order)

Lead Time:

Quantity(Kilograms)	1 - 17000	17001 - 25500	>25500
Est. Time(days)	5	10	To be negotiated

Customization:

Customized logo(Min. Order: 17000 Kilograms)

Customized packaging(Min. Order: 17000 Kilograms)

Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,[www.zhuoxingchem.com](http://www.zhuoxingchem.com)



**Shandong Zhuoxing Chemical Co., Ltd.**  
**Zibo Zhuoxing Enterprises Co., Ltd.**

### Quality Specification

Item	Unit	result
Appearance	/	White powder
Density	kg/m <sup>3</sup>	1500±50
PH	/	6.0±1.0
Solid Content	%	97.0±1.0
Initial Water Reducing Ratio	%	≥22
Cl-	%	≤0.02
Alkali content	%	≤0.3
Moisture content	%	≤3.0

### Characteristics

(1)SPS-15 Polycarboxylate ether superplasticizer powder with solid content 97% min. is especially optimized for plastification and water reduction of cementitious construction materials. (2)Having a good thermostability to 300°C (three hundred degree celsius centigrade). (3)Provide an excellent development of early strength and high strength. (4)With a good dispersion, an excellent adaptability to different cements, and good water-reducing properties。 (5)High

Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,[www.zhuoxingchem.com](http://www.zhuoxingchem.com)



**Shandong Zhuoxing Chemical Co., Ltd.**  
**Zibo Zhuoxing Enterprises Co., Ltd.**

durability: reduce mortar water-cement ratio, improve durability, reduce shrinkage and variations, reduce post-curing mortar shrinkage cracking.

### **Application**

1.It is used for gypsum based and cement based dry mix mortar. It can also be used for oil well cementing operation. 2.It is especially for cementitious self-levelling underlayments (SLU), plasters and masonry, non-shrink grouts, self-levelling floor screeds, repair mortars, injection mortars, dry mix concrete, tiles adhesives and joint fillers.



Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,[www.zhuoxingchem.com](http://www.zhuoxingchem.com)